

HIKVISION Camara PTZ IP 4MP 4× IR IK10 IP66 H.265+



HIKVISION

Marca: Hikvision

Código del producto: 1943, DS-2DE2A404IW-DE3 (2.8-12m

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Short Description

- 1/3 "de barrido progresivo CMOS
- Resolución de hasta 2560 × 1440 @ 25fps
- Zoom óptico 4 ×, zoom digital 16 ×
- 120 dB WDR, 3D DNR, HLC, EIS, exposición regional, enfoque regional
- 12 VDC y PoE
- Hasta 20 m de distancia IR
- IK10, IP66
- Soporta compresión de video H.265 + / H.265
-

Descripción

- 1/3 "de barrido progresivo CMOS
- Resolución de hasta 2560 × 1440 @ 25fps
- Zoom óptico 4 ×, zoom digital 16 ×
- 120 dB WDR, 3D DNR, HLC, EIS, exposición regional, enfoque regional
- 12 VDC y PoE
- Hasta 20 m de distancia IR
- IK10, IP66
- Soporta compresión de video H.265 + / H.265

Camera

Image Sensor:	1/3" progressive scan CMOS
Effective Pixels:	2560(H)×1440(V)
Signal System:	PAL/NTSC
Minimum Illumination:	Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR
White Balance:	Auto/Manual/ATW (Auto- Tracking White Balance)/I ndoor/Outdoor/Fluorescent Lamp/Sodium Lamp
AGC:	Auto/Manual
HLC:	Support
WDR:	120dB
Shutter Time:	50Hz: 1/1 s to 1/30,000 s 60Hz: 1/1 s to 1/30,000 s
Day& Night:	ICR
Digital Zoom:	16×
Privacy Mask:	24 programmable privacy masks
Auto Focus:	Auto / Semi-automatic / Manual
Lens	
Focal Length:	2.8 to 12mm, 4× optical zoom
Zoom Speed:	Approx. 2s (optical lens, wide-tele)
Field of View:	Horizontal field of view: 100° to 33° (Wide-Tele) Vertical field of view: 53° to 18° (Wide-Tele) Diagonal field of view: 119° to 37.5° (Wide-Tele)
Minimum Working Distance:	10 to 1500mm (wide-tele)
Aperture Range:	F1.6 to F2.7

Pan & Tilt	
Pan Range:	0° to 330°
Pan Speed:	Configurable, from 0.1°/s to 100°/s, Preset speed: 100°/s
Tilt Range:	Tilt: 0°~90°
Tilt Speed:	Configurable, from 0.1°/s to 100°/s Preset Speed: 100°/s
Proportional Zoom:	Rotation speed can be adjusted automatically according to zoom multiples
Number of Preset:	300
Power-off Memory:	Support
Infrared	
IR Distance:	20m
IR irradiation angle:	Adjustable by zoom
Input & Output	
Audio Input:	1-ch audio input
Audio Output:	1-ch audio output
Network	
Ethernet:	10Base -T, /100Base-TX, RJ45 Connector
Max.Image Resolution:	2560 × 1440
Main Stream:	50Hz: 25fps (2560 × 1440, 2048 × 1536, 1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 24fps (2560 × 1440), 30fps (2048 × 1536, 1920 × 1080, 1280 × 960, 1280 × 720)
Sub Stream:	50Hz: 25fps(704×576, 640x480,352×288); 60Hz: 30fps(704×480, 640x480,352×240)

Third Stream:	50Hz: 25fps (1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (1280 × 720, 704 × 480, 640 × 480, 352 × 240)
Video Compression:	Main Stream: H.265+/H.265/H.264+/H.264 Sub-Stream: H.265/H.264/MJPEG Third Stream: H.265/H.264/MJPEG
ROI encoding:	Support 2 areas with adjustable levels
Audio Compression:	G.711ulaw/G.711alaw/G.726/MP2L2/G.722
Audio Mode:	OFF/Audio input/Audio output
Protocols:	IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour
Simultaneous Live View:	Up to 20 channels
Three-Stream:	Support
Storage:	Built-in memory card slot, support Micro SD/SDHC/SDXC, up to 256 GB
User/Host:	Up to 32 users, 3 levels: Administrator, Operator and User
Security Measures:	User Authentication (User ID and Password), Host Authentication (MAC address), HTTPS Encryption, IEEE 802.1x Port-Based Network Access control, IP address Filtering

General

Power Supply:

12 VDC & PoE

Power Consumption:

Max.: 12 W (Max. 3.9 W for IR)

Working

-20°C to 60°C (-4°F to

Temperature/Humidity:

140°F)

Protection Level:

IP66 Standard, IK10, TVS
4000V Lightning
Protection, Surge
Protection and Voltage
Transient Protection

Material:

Aluminum alloy, PC,
PC+ABS

Dimensions:

? 130.7 mm × 101.7 mm (?
5.15" × 4.00")

Weight (approx.):

Approx. 0.53 kg (1.17 lb)