

HIKVISION Camara PTZ IP 2MP 25X PoE IR100m H.256+ (incluye brazo y fuente)



HIKVISION

Marca: Hikvision

Código del producto: 1941, DS-2DE4225IW-DE

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Short Description

- 1 / 2.8 "CMOS de exploración progresiva
- Resolución de hasta 1920 × 1080 a 30 fps.
- Min. iluminación: Color: 0.005 Lux @ (F1.6, AGC ON)
- B / W: 0.001 Lux @ (F1.6, AGC ON) 0 Lux con IR
- Zoom óptico 25 ×, zoom digital 16 ×
- WDR, HLC, BLC, 3D DNR, Desempañar, EIS, Exposición regional, Enfoque regional
- Hasta 100 m de distancia IR
- 12 VDC y PoE
- Soporta H.265 + / H.265

Descripción

- 1 / 2.8 "CMOS de exploración progresiva
- Resolución de hasta 1920 × 1080 a 30 fps.
- Min. iluminación: Color: 0.005 Lux @ (F1.6, AGC ON)
- B / W: 0.001 Lux @ (F1.6, AGC ON) 0 Lux con IR
- Zoom óptico 25 ×, zoom digital 16 ×

- WDR, HLC, BLC, 3D DNR, Desempañar, EIS, Exposición regional, Enfoque regional
- Hasta 100 m de distancia IR
- 12 VDC y PoE
- Soporta H.265 + / H.265

Camera

Image Sensor:	1/2.8" HD progressive scan CMOS
Effective Pixels:	1920(H)x1080(V)
Signal System:	PAL/NTSC
Minimum Illumination:	Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001Lux @(F1.6, AGC ON) 0 Lux with IR
White Balance:	Auto/Manual/ATW (Auto-Tracking White Balance)/Indoor/Outdoor/Fluorescent Lamp/Sodium Lamp
AGC:	Auto/Manual
BLC:	ON/OFF
HLC:	Support
Smart defog:	Support
WDR:	120dB
Shutter Time:	1-1/10,000s
Day& Night:	ICR
Digital Zoom:	16X
Privacy Mask:	24 programmable privacy masks; optional multiple colors and mosaics
Auto Focus:	Auto / Semi-automatic / Manual
Lens	
Focal Length:	4.8 mm to 120 mm, 25× optical zoom
Zoom Speed:	Approx. 3.6 s (optical lens, wide-tele)
Field of View:	Horizontal field of view: 57.6° to 2.5° (Wide-Tele)

Minimum Working
Distance:
Aperture Range:

Vertical field of view:
34.4° to 1.4° (Wide-Tele)
Diagonal field of view:
64.5° to 2.9° (Wide-Tele)
10-1,500mm(Wide-Tele)

F1.6 to F3.5

Pan & Tilt
Pan Range:
Pan Speed:

360°endless
Configurable, from 0.1°/s
to 80°/s,
Preset speed: 80°/s

Tilt Range:
Tilt Speed:

-15°-90° (Auto Flip)
Configurable, from 0.1°/s
to 80°/s,
Preset speed: 80°/s

Proportional Zoom:

Rotation speed can be
adjusted automatically
according to zoom
multiples

Number of Preset:
Patrol:

300
8 patrols, up to 32 presets
per patrol

Pattern:

4 pattern scans, record
time over 10 minutes for
each scan

Power-off Memory:
Park Action:

Support
Preset/Pattern Scan/Patrol
Scan/Auto Scan/Tilt
Scan/Random Scan/Frame
Scan/Panorama Scan

PTZ Position Display:

ON/OFF

Infrared
IR Distance:
IR irradiation angle:

100m
Adjustable by zoom

Input & Output

Audio Input:

1-ch audio input

Audio Output:

1-ch audio output

Network

Ethernet:

10Base -T, /100Base-TX,
RJ45 Connector

Max.Image Resolution:

1920×1080

Main Stream:

50Hz:25fps (1920×1080,1
280×960,1280×720), 50fps
(1280×960,1280×720) ;
60Hz:30fps(1920×1080,12
80×960,1280×720), 60fps
(1280×960,1280×720)

Sub Stream:

50Hz: 25fps(704×576,
640x480,352×288); 60Hz:
30fps(704×480,
640x480,352×240)

Third Stream:

50Hz: 25fps(1920×1080,
1280×960, 1280×720,
704×576,
640x480,352×288)
60Hz: 30fps(1920×1080,
1280×960, 1280×720,
704×576,
640x480,352×288)

Video Compression:

Main Stream: H.265+/H.26
5/H.264+/H.264

Sub-Stream:

H.265/H.264/MJPEG

Third Stream:

H.265/H.264/MJPEG

ROI encoding:

Support 4 areas with
adjustable levels

Audio Compression:

G.711alaw/G.711ulaw/G.7
22.1/G.726/MP2L2/PCM

Audio Mode:

OFF/Audio input/Audio
output

Protocols:

IPv4/IPv6, HTTP, HTTPS,
802.1x, Qos, FTP, SMTP,
UPnP, SNMP, DNS,

Simultaneous Live View:	DDNS, NTP, RTSP,
Three-Stream:	RTCP, RTP, TCP, UDP,
Storage:	IGMP, ICMP, DHCP,
	PPPoE, Bonjour
	Up to 20 channels
	Support
	Built-in memory card slot,
	support Micro
	SD/SDHC/SDXC, up to
	256 GB
User/Host:	Up to 32 users, 3 levels:
	Administrator, Operator
	and User
Security Measures:	User authentication (ID
	and PW), host
	authentication (MAC
	address)
Client GUI	
Client:	iVMS-4200, iVMS-4500,
	iVMS-5200, Hik-Connect
Web Browser:	IE 8 to 11, Chrome 31.0 to
	44, Firefox 30.0 to 51
General	
Language:	English
Power Supply:	12VDC, PoE+
Power Consumption:	Max.: 18 W (Max. 7 W for
	IR)
Working	-30
Temperature/Humidity:	?-65?(-22?-149?)(outdoor)
	90% or less
Protection Level:	IP66 standard (outdoor
	dome)
	TVS 4,000V lightning
	protection, surge
	protection and voltage
	transient protection
Material:	ADC 12, PC, PC+10%GF

Dimensions:

? 164.5 mm × 290 mm (?
6.48" × 11.42")

Weight (approx.):

Approx. 2 kg (4.41 lb)