

HIKVISION Camera Domo Network 3 MP IR Vari-focal 2.8mm to 12mm Easy IP



HIKVISION

Marca: Hikvision

Código del producto: 1888, DS-2CD2735FWD-IZS(2.8-12mm

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Short Description

Cámara minidomo de tecnología IP y resolución 3 Megapíxeles (2048x1536 @25ips).

Óptica varifocal 2.8-12mm motorizada.

Compresión H.265+/H.265/H.264+/H.264.

Descripción

Cámara minidomo de tecnología IP y resolución 3 Megapíxeles (2048x1536 @25ips).

Óptica varifocal 2.8-12mm motorizada.

Compresión H.265+/H.265/H.264+/H.264.

- Sensor CMOS 1/2.8" ultra low light con conmutación día/noche mediante filtro mecánico.
- Sensibilidad en color 0,005 Lux Color (F1.2, AGC ON).
- LEDS IR alcance 30m.
- WDR real 120dB, BLC, Defog, EIS, 3D DNR, ROI.

Especificaciones de red:

- Salida Ethernet 10/100Mbps

- Triple streaming de video
- Servidor Web integrado Internet Explorer
- Compatible con ONVIF, ISAPI.
- Soporta tarjeta SD hasta 128GB (tarjeta no incluida).

Detección:

- Básica: movimiento, tamper de vídeo, excepciones.
- Avanzada: intrusión, cruce de línea, objeto abandonado, objeto sustraído, detección facial.

Especificaciones generales:

- Salida de video compuesto (75Ohm, BNC).
- Alarmas: 1 entrada y 1 salida, audio: 1 entrada y 1 salida.
- Nivel de protección: IP67, antivandálico IK10.
- Instalación en exterior.
- Alimentación 12 VDC max 750mA y PoE (802.3 af).
- Dimensiones: Ø 153.4 × L 133.1 mm.

Camera

Image Sensor:

1/2.8" Progressive Scan
CMOS

Signal System:

PAL/NTSC

Min. Illumination:

Color: 0.005 Lux @ (F1.2,
AGC ON), 0 Lux with IR
Color: 0.009 Lux @ (F1.6,
AGC ON), 0 Lux with IR

Shutter time:

1/3 s to 1/100,000 s

Slow shutter:

Support

Lens:

2.8 to 12 mm

Horizontal field of view:

97°to 33°

Vertical field of view: 69°to
25°

Diagonal field of view:

130°to 41°

Lens Mount:

Ø14

Adjustment Range:	Pan: 0° to 355°, tilt: 0° to 75°, rotate: 0° to 355°
Day& Night:	IR Cut Filter
Wide Dynamic Range:	120 dB
Digital noise reduction:	3D DNR
Focus:	Auto
Compression Standard	
Video Compression:	H.265+/H.265/H.264+/H.264/MJPEG
Video bit rate:	32Kbps~16Mbps
Audio Compression:	G.711/G.722.1/G.726/MP2L2/PCM
Audio bit rate:	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)
Triple Streams:	Yes
Image	
Max. Image Resolution:	2048×1536
Frame Rate:	50Hz: 25fps (2048 × 1536, 1920 × 1080, 1280 × 720) 60Hz: 30fps (2048 × 1536, 1920 × 1080, 1280 × 720)
Sub Stream:	50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)
Third Stream:	50Hz: 25fps (1280 × 720, 640 × 360, 352 × 288) 60Hz: 30fps (1280 × 720, 640 × 360, 352 × 240)
Image Enhancement:	BLC/3D DNR/BLC
Image Settings:	Rotate mode, saturation, brightness, contrast, sharpness and white balance adjustable by client software or web browser
ROI:	Support 1 fixed region for main stream and sub stream separately
Day/Night Switch:	Day/Night/Auto/Schedule/Tri

gged by Alarm In

Network

Network Storage:

microSD/SDHC/SDXC card
(128G), local storage and
NAS (NFS,SMB/CIFS),
ANR

Alarm Trigger:

Motion detection, tampering
alarm, HDD full, HDD error,
network disconnected, IP
address conflicted, illegal
login

Protocols:

TCP/IP, ICMP, HTTP,
HTTPS, FTP, DHCP, DNS,
DDNS, RTP, RTSP, RTCP,
PPPoE, NTP, UPnP, SMTP,
SNMP,
IGMP, 802.1X, QoS, IPv6,
Bonjour

General Function:

One-key recovery, Anti-
Flicker, three streams,
heartbeat, mirror, password
protection, video
mask, Watermark, IP address
filtering

System Compatibility:

ONVIF (Profile S, Profile G),
ISAPI

Interface

Audio:

1 input (line in, 3.5 mm), 1
output (line out, 3.5 mm),
mono sound

Communication Interface:

1 RJ45 10M / 100M Ethernet
interface

Alarm:

1 alarm input, 1 alarm output
(max. 12 VDC, 30 mA),
terminal block

Video Output:

1Vp-p Composite
Output(75%/CVBS) (For
adjustment only)

On-board storage:

Built-in Micro
SD/SDHC/SDXC slot, up to

128 GB

Reset Button:

Yes

Audio

Environment Noise Filtering:

Support

Audio Sampling Rate:

8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz

Smart Feature-set

Behavior Analysis:

Line crossing detection,
Intrusion detection,
Unattended baggage
detection, Object removal
detection

Line Crossing Detection:

Cross a pre-defined virtual
line

Intrusion Detection:

Enter and loiter in a pre-
defined virtual region

Unattended Baggage:

Objects left over in the pre-
defined region such as the
baggage, purse, dangerous
materials

Object Removal:

Objects removed from the pre-
defined region, such as the
exhibits on display.

Exception Detections:

Scene change detection

Recognition:

Face Detection

General

Operating Conditions:

-30 °C ~ 60 °C (-22 °F ~ 140
°F)

Humidity 95% or less (non-
condensing)

Power Supply:

12 VDC $\pm$ 25%, PoE
(802.3af Class3)

Power Consumption:

12 VDC, 0.75A, max. 9.5W
PoE (802.3af, 36V to 57V),
0.1A to 0.3A, max. 11W

Impact Protection:

IK10

Weather Proof:

IP67

IR Range:

Up to 30m

Dimensions:

153.4 × 133.1 mm (6.04" ×

5.24")

Camera: 1287 g (2.84 lb.)

Weight: