

# UNIVIEW 4MP Fisheye Fixed Dome Network Camera 431



**Marca:** Hikvision

**Código del producto:** 1691, IPC814SR-DVPF16

**Disponibilidad:** In Stock

**Peso:** 0.00kg

**Dimensiones:** 0.00cm x 0.00cm x 0.00cm

## Descripción

IPC814SR-DVPF16

Camera

Image sensor

1/3", progressive scan, 4.0 megapixel, CMOS

Lens

1.6mm@ F1.6

Angle of View (H)

180°

Shutter

Auto/Manual? shutter time? 1/6 s ~ 1/100000 s

Minimum Illumination

Colour: 0.01 Lux (F1.6, AGC ON)

0 Lux with IR

Day / Night

IR-cut filter for day & night function

Digital noise reduction

2D/3D DNR

S/N

>55dB

IR Range

UP to 10m (33ft)

Defog

Digital Defog

WDR

120dB

Video

Compression

Ultra265, H.265, H.264, MJPEG

H.264 code profile

Baseline profile, Main Profile, High Profile

|                        |                                                                                                                                                                        |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frame Rate             | Main<br>Stream:(2560×1440):<br>Max.25fps;<br>Sub Stream:(1920×1080) :<br>Max.25fps;<br>Third Stream:D1(720 x<br>576): Max.25 fps                                       |
| BLC                    | Supported                                                                                                                                                              |
| OSD                    | Up to 8 OSDs                                                                                                                                                           |
| ROI                    | Up to 8 areas                                                                                                                                                          |
| Privacy Mask           | Up to 8 areas                                                                                                                                                          |
| Motion Detection       | Up to 4 areas                                                                                                                                                          |
| General Function       | Watermark, IP Address<br>Filtering, Tampering<br>Alarm, Alarm input,<br>Alarm output, Access<br>Policy, ARP Protection,<br>RTSP Authentication,<br>User Authentication |
| Audio                  |                                                                                                                                                                        |
| Audio Compression      | G.711                                                                                                                                                                  |
| Two-way audio          | Supported                                                                                                                                                              |
| Suppression            | Supported                                                                                                                                                              |
| Sampling Rate          | 8 KHZ                                                                                                                                                                  |
| Storage                |                                                                                                                                                                        |
| Edge Storage           | Micro SD, up to 128GB                                                                                                                                                  |
| Network Storage        | ANR                                                                                                                                                                    |
| Network                |                                                                                                                                                                        |
| Protocols              | IPv4, IGMP, ICMP, ARP,<br>TCP, UDP, DHCP,<br>PPPoE, RTP, RTSP,<br>RTCP, DNS, DDNS,<br>NTP, FTP, UPnP, HTTP,<br>HTTPS, SMTP, 802.1x,<br>SNMP                            |
| Compatible Integration | ONVIF(Profile S, Profile<br>G), API                                                                                                                                    |
| Live View Display      |                                                                                                                                                                        |
| Mount Type             | Support table, wall, and<br>ceiling                                                                                                                                    |
| Interface              |                                                                                                                                                                        |
| Audio I/O              | Audio interface                                                                                                                                                        |

|                     |                                                                                                                                                                |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                     | Input: impedance 35 k $\Omega$ ;<br>amplitude 2 V [p-p]<br>Output: impedance 600 $\Omega$ ;<br>amplitude 2 V [p-p]<br>3 built-in omnidirectional<br>microphone |
| Alarm I/O           | 1 / 1                                                                                                                                                          |
| Built-in Mic        | Supported                                                                                                                                                      |
| Built-in Speaker    | Supported                                                                                                                                                      |
| Video Output        | 1 BNC, impedance 75 $\Omega$ ;<br>amplitude 1 V [p-p]                                                                                                          |
| Network             | 1 RJ45 10M/100M Base-<br>TX Auto-adaptive<br>Ethernet                                                                                                          |
| General             |                                                                                                                                                                |
| Power               | DC12V $\pm$ 25%,PoE(IEEE<br>802.3af)<br>Power consumption: Max.<br>11 W                                                                                        |
| Dimensions (Ø x H)  | 125x 43.7 mm (4.9" x<br>1.7")                                                                                                                                  |
| Weight              | 0.39kg(0.86lb)                                                                                                                                                 |
| Working Environment | -40°C ~60°C (-40°F ~<br>140°F), Humidity<br>:10%~95% RH                                                                                                        |
| Ingress Protection  | IP66                                                                                                                                                           |
| Vandal Resistant    | IK10                                                                                                                                                           |
| Reset Button        | Supported                                                                                                                                                      |