

UNIVIEW, 4MP Motorized VF 2.8~12mm IR Bullet Camera 30m H.265 WDR



Marca:

Código del producto: 1613, IPC2324EBR-DPZ28

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Short Description

Óptica

- Funcionalidad día / noche Smart IR, hasta 30 m (98 pies) de distancia
- IR Hasta 120 dB de WDR óptico (rango dinámico amplio)

Descripción

Óptica

- Funcionalidad día / noche Smart IR, hasta 30 m (98 pies) de distancia
- IR Hasta 120 dB de WDR óptico (rango dinámico amplio)

Compresión

- Ultra 265, H.265, H.264, MJPEG
- Algoritmo inteligente incorporado
- Triple flujo
- ROI (región de interés)
- 9:16 modo corredor
- OSD personalizado

Red

- Conformidad ONVIF
- Estructura
- Amplio rango de voltaje de $\pm 25\%$
- IP67

- Características:

Camera	IPC2324EBR-DP
Sensor	1/3", progressive scan, 4megapixel, CMOS
Lens	2.8~12mm?AF automatic focusing and motorized zoom lens
Angle of View(H)	91°~27°
Shutter	Auto/Manual, 1/6~1/100000 s
MinimumIllumination	Colour: 0.02 Lux (F1.4, AGC ON)
	0 Lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>52dB
IR Range	Up to 30m (98 ft) IR range
Defog	Digital Defog
WDR	Optical WDR (up to 120 dB)
Video	
Video Compression	Ultra 265,H.265, H.264,MJPEG
Frame Rate	Main Stream:4MP (2592×1520): Max. 20 fps?4MP (2560×1440): Max. 25 fps?3MP (2048×1520): Max. 30 fps;
	Sub Stream:2MP (1920×1080): Max. 30 fps;
	Third Stream:D1(720×576) : Max. 30fps
9:16 Corridor Mode	Supported
HLC	Supported
BLC	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 areas

ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Smart	
Behavior Detection	Intrusion, cross line, motion detection
Exception Detection	Audio detection
Intelligent Identification	Face detection, Defocus, Scene Change
Statistical Analysis	People counting
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio	
Audio Compression	G.711
Two-way audio	Supported
Suppression	Supported
Sampling Rate	8 KHZ
Storage	
Edge Storage	Micro SD, up to 128 GB
Network Storage	ANR
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible Integration	ONVIF(Profile S, Profile G),API
Interface	
Audio I/O	Audio cable Input: impedance 35 k Ω ; amplitude 2 V [p-p] Output: impedance 600 Ω ; amplitude 2 V [p-p]
Alarm I/O	1/ 1
Network	10M/100M Base-TX Ethernet
Video Output	1 BNC, impedance 75 Ω ; amplitude 1 V [p-p]
General	
Power	12 V DC $\pm$ 25%, PoE (IEEE802.3 af) Power consumption: Max 8W
Dimensions (L $\times$ W $\times$ H)	253.4 $\times$ 86 $\times$ 71.7 mm (9.98" $\times$ 3.4" $\times$ 2.8")
Weight	0.58kg (1.28lb)

Working Environment

-35°C ~ +60°C (-31°F ~ 140°F),

Humidity ? 95% RH(non-condensing)

Ingress Protection

IP67