

HIKVISION NVR Plug and Play 16ch- 6MP - 2 SATA - 8ch PoE



Marca: Hikvision

Código del producto: 1945, DS-7616NI-E2/16P

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm



Short Description

- Cámaras de red de terceros compatibles
- Resolución de hasta 6 megapíxeles de grabación.
- Salida HDMI y VGA a hasta 1920 × 1080P resolución
- Se pueden conectar cámaras de red de 16-ch con ancho de banda entrante de 160M
- Hasta 2 interfaces SATA
- Plug & Play con hasta 8 redes PoE independientes interfaces

Descripción

- Cámaras de red de terceros compatibles
- Resolución de hasta 6 megapíxeles de grabación.
- Salida HDMI y VGA a hasta 1920 × 1080P resolución
- Se pueden conectar cámaras de red de 16-ch con ancho de banda entrante de 160M
- Hasta 2 interfaces SATA
- Plug & Play con hasta 8 redes PoE independientes interfaces
- Soporte de detección de red, incluido el retardo de red, pérdida de paquetes, etc.

Video/Audio Input

Two-way audio input:

IP video input:

1-ch, RCA (2.0 Vp-p, 1k?)

16-ch

Network

Remote connection:	128
Incoming bandwidth:	160Mbps
Outgoing bandwidth:	80Mbps

Video/Audio Output

HDMI/VGA output:	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
Recording Resolution:	6MP/5MP/4MP/3MP/1080 P/UXGA/720P/VGA/4CIF /DCIF/2CIF/CIF/QCIF
Frame Rate:	Main stream: 50 fps (P) / 60 fps (N) Sub-stream: 50 fps (P) / 60 fps (N)
Audio Output:	1-ch, RCA (Linear, 1k?)
Synchronous Playback:	16-ch

Decoding

Capability:	6-ch@1080P
Live view / Playback:	6MP/5MP/3MP/1080P/UX GA/720P/VGA/4CIF/DCI F/2CIF/CIF/QCIF

Hard Disk

SATA:	2 SATA interfaces for 2 HDDs
Capacity:	Up to 6TB capacity for each HDD

External Interface

Network Interface:	1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
--------------------	---

USB Interface:	1 × USB 2.0 and 1 × USB 3.0
Alarm In:	4-ch
Alarm Out:	1-ch(optional)
POE	
Supported Standard:	AF and AT
Interface:	16 independent 100 Mbps PoE network interfaces
Max. Power:	200W
General	
Power Supply:	100~240VAC
Consumption(without hard disk and POE):	? 15W
Working Temperature:	-10 oC ~ +55 oC (+14 oF~ + 131 oF)
Working Humidity:	10 % ~ 90 %
Chassis:	19-inch rack-mounted 1U chassis
Dimensions:	445 × 290 × 45mm (17.5 × 11.4 × 1.8 inch)
Weight(without HDD):	? 1 Kg (2.2 lb)