

# NVR 8CH H.265 1 x 4K@3060



**Marca:**

**Código del producto:** 1677, NVR301-08L-P8

**Disponibilidad:** In Stock

**Peso:** 0.00kg

**Dimensiones:** 0.00cm x 0.00cm x 0.00cm

## Short Description

- 4/8/16-channel input
- Plug & Play with 4/8 independent PoE network interfaces
- Third-party IP cameras supported with ONVIF conformance
- Support 1-ch HDMI, 1-ch VGA, HDMI at up to 4K(3840×2160) resolution
- Up to 8 Megapixels resolution recording
- Support H.265/H.264 video formats
- Accurate retrieval, instant playback
- 1 SATA HDD up to 6 TB
- Support for P2P, UPnP, NTP, DHCP, PPPoE

## Descripción

- 4/8/16-channel input
- Plug & Play with 4/8 independent PoE network interfaces
- Third-party IP cameras supported with ONVIF conformance
- Support 1-ch HDMI, 1-ch VGA, HDMI at up to 4K(3840×2160) resolution
- Up to 8 Megapixels resolution recording
- Support H.265/H.264 video formats
- Accurate retrieval, instant playback
- 1 SATA HDD up to 6 TB
- Support for P2P, UPnP, NTP, DHCP, PPPoE

|                          |               |                      |               |
|--------------------------|---------------|----------------------|---------------|
| Model                    | NVR301-04L-P4 | <b>NVR301-08L-P8</b> | NVR301-16L-P8 |
| <b>Video/Audio Input</b> |               |                      |               |
| IP Video                 | 4-ch          | 8-ch                 | 16-ch         |
| Input                    |               |                      |               |

Two-way 1-ch, RCA  
Audio Input

**Network**

Incoming 40Mbps 60Mbps 60Mbps  
Bandwidth

Outgoing 64Mbps 64Mbps 80Mbps  
Bandwidth

Remote 128  
Users

**Video/Audio Output**

HDMI/VGA HDMI:  
Output

4K (3840x2160) /30Hz, 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz

VGA:

1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz

Recording 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF  
Resolution

Audio Output 1-ch, RCA

Synchronous 4-ch 8-ch 16-ch

Playback

**Decoding**

Compression H.265/H.264

Live view/ 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Playback

Capability 1 x 4K@30, 3 x 4MP@20, 4 x 1080p@25, 8 x 720p@25, 16 x D1

**Hard Disk**

SATA 1 SATA interface

Capacity up to 6TB for each disk

**External Interface**

Network 1 RJ-45 10M/100M self-adaptive Ethernet Interface  
Interface

USB Rear panel? 2 x USB2.0  
Interface

**PoE**

Interface 4 independent 100 Mbps 8 independent 100 Mbps PoE network interfaces  
PoE network interfaces

Max Power Max 30W for single port Max 30W for single port

|                        |                                         |  |                                      |
|------------------------|-----------------------------------------|--|--------------------------------------|
|                        | Max 54W in total ( 13.5W for each )     |  | Max 108W in total ( 13.5W for each ) |
| Supported Standard     | IEEE 802.3at, IEEE 802.3af              |  |                                      |
| <b>General</b>         |                                         |  |                                      |
| Power Supply           | 48V DC                                  |  | 52V DC                               |
| Consumption            | ? 8 W                                   |  |                                      |
| ( without HDD )        |                                         |  |                                      |
| Working Temperature    | -10°C ~ + 55°C ( +14°F ~ +131°F )       |  |                                      |
| Working Humidity       | 10% ~ 90%                               |  |                                      |
| Dimensions             | 42 × 205 × 205mm ( 1.7" × 8.1" × 8.1" ) |  |                                      |
| Weight ( without HDD ) | 0.59kg ( 1.3 lb )                       |  | ? 0.68 Kg ( 1.50 lb )                |