

UTEPO Switch POE 16FE + 2 GIGA 250m


Marca:

Código del producto: 1684,
UTP1-SW16-TP300

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Short Description

Conmutador Ethernet PoE no administrado junto con puertos PoE de enlace descendente 16 * 10 / 100Base-TX y puertos Ethernet de enlace ascendente 2 * 10/100 / 1000Base-T con 302 watt 802.3at PoE +, así como 1 Combo Gigabit adicional Puerto. El presupuesto total de energía PoE es de hasta 270 vatios. Admite la gestión de PoE basada en la web y la pantalla LED de

Descripción

Model

UTP1-SW16-TP300

Downstream Ports

16* 10/100Base-TX(PoE)

Uplink Ports

2*10/100/1000Base-T and 1*1000Base-X/SFP(Combo)

Network Standard

IEEE802.3 ?IEEE802.3u?IEEE802.3ab?IEEE802.3z?IEEE802.3X

Switch Capacity

7.2Gbps

Throughput

5.36Mpps

Switch Processing Scheme

Store and Forward

Memory Buffer

2.75M

MAC Table

4K

PoE Standard Type

802.3af/at(PSE) End-span

One-key CCTV mode

all the downlink ports can only communicate with uplink ports ;retrain the network storm to 3Mbps; extend transmission distance of the downlink ports to 250m max.

Power Pin Assignment

1/2(+)?3/6(-)

PoE Power Output	54V DC , 30 watts max
PoE Budge	270 watts max
PoE Management	Via Web(Default IP Address 192.168.1.200) to check, on/off and adjust each port PoE output
Lightning protection	6KV Execute?IEC61000-4-5
ESD	6KV Contact discharge 8KV Air discharge Execute?IEC61000-4-2
Power Supply	100~240V AC?50/60Hz
Power Dissipation	?300W(Including PoE)
Work Temperature	-10?~50?
Storage Temperature	-40?~85?
Humidity(Non-condensin)	5%-95%
Dimension?L×W×H?	442mm×207mm×44.5mm
Weight	2.69kg
Regulator	CE?FCC?ROHS