UTEPO, 8 Ports Industrial Full Gigabit PoE Managed Switch



Marca: Código del producto: 1683, UTP7308GE-PoE Disponibilidad: In Stock Peso: 0.00kg Dimensiones: 0.00cm x 0.00cm x 0.00cm

Short Description

UTP7308GE-POE is 8 Ports Industrial Full Gigabit PoE Managed SwitchProvide 8* 10/100/1000Base-T Ethernet ports(PoE), 4 * 1000BASE-X SFP ports(Unlinks). The switch provides up to 4Mbit cache, Support 4K high-definition video transmission. Besides, the 8 downlink PoE ports support IEEE802.3af/at standard. PoE output power of single port is up to 60W

Descripción Model Number Downlink Ports Uplink Ports Network Standard

Bandwidth Packet Transfer Rate Exchange Way Buffer MAC Address PoE Standard PoE Power Supply PoE Line Pair

UTP7308GE-POE

8* 10/100/1000Base-T PoE RJ45 ports 4*1000Base-X SFP ports IEEE802.3 ?IEEE802.3u?IEEE802.3ab?IEE E802.3Z?IEEE802.3X? IEEE 802.1Q IEEE 802.1p IEEE 802.3ad ?IEEE 802.1D?IEEE 802.1X 24Gbps 18Mpps Storage& Transfer 4M 8K 802.3af/at End-span 1/2(+)?3/6(-) PoE Output alarm signal output by relay

Surge Immunity ESD Protection

Input Voltage Power Consumption Operation Temperature Storage Temperature Operation Humidity Dimension(LxWxH) Weight Authentication Software Parameter? Port Management VLAN QoS

Multicast Management

POE Management

Sigle Port ? 30W PoE Support relay alarm for power off, ports network link-off, ports PoE off ?Set by Web Software? 6KV Per: IEC61000-4-5 ESD Level 4 Per: IEC61000-4-2

RS Level 4 Per: IEC61000-4-3

EFT Level 4 Per: IEC61000-4-4

CS Level 4 Per: IEC61000-4-6 48~57V DC Self consumption?15W -40?~75? -40?~85? 5%-95% ?no-condensation? 159mm×110mm×46.5mm 1kg CE?FCC?ROHS

Support Port Enable/Disable; Support Port Rate Settings; Support Port Full-duplex Mode; Support IEEE802.3x Flow Control; Support Port Name Change; Support 4K VLAN Support 802.1Q Protocol-Based VLAN; Support Port-Based VLAN; Support QoS; Support 8-Level Priority management for switching; Support WRR; Support 820.1P and DSCP Priority; Support SNMP V1/V2/V3 Protocol; Support IGMP Snooping; Support Total Power Consumption Control; Support PoE ON/OFF; Support Single Port 60W/30W max. Power Change and Port Output Priority;

alarm signal output by relay	Support relay alarm for power off, ports network link-off, ports PoE off
alarm signal output by relay Safety Character System Management& Maintenance	 network link-off , ports PoE off Support IP?MAC?Port?VLAN Combination and Binding; Support MAC address auto-learning, aging& filter; Support Port Isolation, Port Speed-Limited; Support RSTP; Support Fast-Ring; Support 5 groups of 8-Port trunk; Support RADIUS Authentication& 802.1X Authentication; Support WEB Management, CLR Settings
	and telnet Settings; Support CLR Settings; Support FTP/TFTP/HTTP Web Upgrading; Support Flow Calculate; Support MAC address Form Search; Support IP Address, DNS Server Change Support Username& Password Change; Support History Record, Journal management; Support System settings Backup;