

HIKVISION Camara Mini Domo IP lente fijo 4mm - 4 MP - EXIR- PoE



Marca: Hikvision

Código del producto: 2029, DS-2CD2523GO-IS (4MM)

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

HIKVISION

Short Description

2688 × 1520 a 30 fps

- IR: hasta 10 m • H.265, H.265 +
- 120dB WDR
- Ranura Micro SD / SDHC / SDXC incorporada, hasta 128 GB
- PoE
- EXIR

Descripción

2688 × 1520 a 30 fps

- IR: hasta 10 m • H.265, H.265 +
- 120dB WDR
- Ranura Micro SD / SDHC / SDXC incorporada, hasta 128 GB
- PoE
- EXIR

Camera

Image Sensor:

1/3" Progressive Scan CMOS

Signal System:

PAL/NTSC

Min. Illumination:

Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR

Shutter time:

1/3 s to 1/100,000 s

Slow shutter:

Support

Lens:

2.8 mm: Horizontal field of view: 98°, Vertical field of view: 55°, Diagonal field of view: 114°

4 mm: Horizontal field of view: 78°, Vertical field of view: 42°, Diagonal field of view: 93°

6 mm: Horizontal field of view: 48°, Vertical field of view: 27°, Diagonal field of view: 54°

Lens Mount:

M12

Adjustment Range:

Pan: -30° to +30°, tilt: 0° to 75°, rotate: 0° to 360°

Day& Night:

IR Cut Filter

Wide Dynamic Range:

120 dB

Digital noise reduction:

3D DNR

Focus:

Fixed

Compression Standard

Video Compression:	H.265+/H.265/H.264+/H.264/MJPEG
H.264 code profile:	Main Profile/High Profile
Video bit rate:	256Kbps~16Mbps
Audio Compression:	G.711/G.722.1/G.726/MP2L2/PCM
Audio bit rate:	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)
Triple Streams:	Yes
Image	
Max. Image Resolution:	2688 × 1520
Frame Rate:	50Hz: 25fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080) 60Hz: 30fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080)
Sub Stream:	50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)
Third Stream:	50Hz: 25fps (1280 × 720, 640 × 360, 352 × 288) 60Hz: 30fps (1280 × 720, 640 × 360, 352 × 240)
Image Enhancement:	BLC/3D DNR/ROI/HLC
Image Settings:	Rotate mode, saturation, brightness, contrast, sharpness and white balance adjustable by client software or web browser
ROI:	Support 1 fixed region for main stream and sub-stream separately
Day/Night Switch:	Auto/Schedule/Day/Night/Triggered by Alarm In (-S model)
Network	
Network Storage:	microSD/SDHC/SDXC card

(128G), local storage and NAS (NFS,SMB/CIFS), ANR

Alarm Trigger:

Motion detection, video tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error

Protocols:

TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6

General Function:

One-key reset, Anti-Flicker, heartbeat, mirror, password protection, privacy mask, Watermark, IP address filtering

System Compatibility:

ONVIF (Profile S, Profile G), ISAPI

Interface

Audio:

with -S model?2 Inputs: line in or mic in (built-in microphone), 1 output: line out, mono sound, terminal block

Communication Interface:

1 RJ45 10M / 100M Ethernet interface

Alarm:

with -S model?1 Input: Alarm in, 1 Output: Alarm out (max. 12 VDC, 30 mA), terminal block

On-board storage:

Built-in Micro SD/SDHC/SDXC slot, up to 128 GB

Reset Button:

Yes

Audio

Environment Noise Filtering:

Support

Audio Sampling Rate:

8 kHz/16 kHz/32 kHz/44.1

kHZ/48 kHz

Smart Feature-set Behavior Analysis:	Line crossing detection, intrusion detection
Line Crossing Detection:	Cross a pre-defined virtual line
Intrusion Detection:	Enter and loiter in a pre-defined virtual region
Recognition:	Face Detection
Wi-Fi Specification (-W) Wireless Standards:	IEEE802.11b, 802.11g, 802.11n
Frequency Range:	2.412 GHz to 2.4835 GHz
Channel Bandwidth:	20/40MHz Support
Security:	WPA, WPA2
Transmission Rate:	11b: 11Mbps 11g: 54Mbps 11n: up to 150Mbps
Wireless Range:	50m(depend on environment)
Protocols:	802.11b: DQPSK, DBPSK, CCK 802.11g/n: OFDM /64-QAM,16-QAM, QPSK, BPSK
General	
Operating Conditions:	-30 °C ~ 60 °C (-22 °F ~ 140 °F) Humidity 95% or less (non-condensing)
Power Supply:	12 VDC ± 25%, PoE (802.3af Class3)
Power Consumption:	12 VDC, 0.7A, max. 8.5W, ? 5.5mm coaxial plug power PoE (802.3af, 36V to 57V), 0.3 A to 0.1 A, max. 10W
Impact Protection:	IK08 Protection Level
Weather Proof:	IP66
IR Range:	Up to 10m
Dimensions:	?110 mm × 56.4 mm (?4.3" ×

2.2")

Camera: Approx. 400 g (0.9 l

Weight: