

HIKVISION Camara PTZ IP 2MP 25X PoE IR100m H.256+ (incluye brazo y fuente)



Marca: Hikvision

Código del producto: 1941, DS-2DE4225IW-DE

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

HIKVISION

Short Description

- 1 / 2.8 "CMOS de exploración progresiva
- Resolución de hasta 1920 × 1080 a 30 fps.
- Min. iluminación: Color: 0.005 Lux @ (F1.6, AGC ON)
- B / W: 0.001 Lux @ (F1.6, AGC ON) 0 Lux con IR
- Zoom óptico 25 ×, zoom digital 16 ×
- WDR, HLC, BLC, 3D DNR, Desempañar, EIS, Exposición regional, Enfoque regional
- Hasta 100 m de distancia IR
- 12 VDC y PoE
- Soporta H.265 + / H.265

Descripción

- 1 / 2.8 "CMOS de exploración progresiva
- Resolución de hasta 1920 × 1080 a 30 fps.
- Min. iluminación: Color: 0.005 Lux @ (F1.6, AGC ON)
- B / W: 0.001 Lux @ (F1.6, AGC ON) 0 Lux con IR
- Zoom óptico 25 ×, zoom digital 16 ×

- WDR, HLC, BLC, 3D DNR, Desempañar, EIS, Exposición regional, Enfoque regional
- Hasta 100 m de distancia IR
- 12 VDC y PoE
- Soporta H.265 + / H.265

Camera

Image Sensor:	1/2.8" HD progressive scan CMOS
Effective Pixels:	1920(H)x1080(V)
Signal System:	PAL/NTSC
Minimum Illumination:	Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001Lux @(F1.6, AGC ON) 0 Lux with IR
White Balance:	Auto/Manual/ATW (Auto-Tracking White Balance)/Indoor/Outdoor/Fluorescent Lamp/Sodium Lamp
AGC:	Auto/Manual
BLC:	ON/OFF
HLC:	Support
Smart defog:	Support
WDR:	120dB
Shutter Time:	1-1/10,000s
Day& Night:	ICR
Digital Zoom:	16X
Privacy Mask:	24 programmable privacy masks; optional multiple colors and mosaics
Auto Focus:	Auto / Semi-automatic / Manual
Lens	
Focal Length:	4.8 mm to 120 mm, 25× optical zoom
Zoom Speed:	Approx. 3.6 s (optical lens, wide-tele)
Field of View:	Horizontal field of view: 57.6° to 2.5° (Wide-Tele)

Minimum Working Distance:	Vertical field of view: 34.4° to 1.4° (Wide-Tele)
Aperture Range:	Diagonal field of view: 64.5° to 2.9° (Wide-Tele) 10-1,500mm(Wide-Tele)
Pan & Tilt	F1.6 to F3.5
Pan Range:	360°endless
Pan Speed:	Configurable, from 0.1°/s to 80°/s, Preset speed: 80°/s
Tilt Range:	-15°-90° (Auto Flip)
Tilt Speed:	Configurable, from 0.1°/s to 80°/s, Preset speed: 80°/s
Proportional Zoom:	Rotation speed can be adjusted automatically according to zoom multiples
Number of Preset:	300
Patrol:	8 patrols, up to 32 presets per patrol
Pattern:	4 pattern scans, record time over 10 minutes for each scan
Power-off Memory:	Support
Park Action:	Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan
PTZ Position Display:	ON/OFF
Infrared	
IR Distance:	100m
IR irradiation angle:	Adjustable by zoom

Input & Output

Audio Input:

1-ch audio input

Audio Output:

1-ch audio output

Network

Ethernet:

10Base -T, /100Base-TX,
RJ45 Connector

Max.Image Resolution:

1920×1080

Main Stream:

50Hz:25fps (1920×1080,1280×960,1280×720), 50fps (1280×960,1280×720) ;
60Hz:30fps(1920×1080,1280×960,1280×720), 60fps (1280×960,1280×720)

Sub Stream:

50Hz: 25fps(704×576, 640x480,352×288); 60Hz: 30fps(704×480, 640x480,352×240)

Third Stream:

50Hz: 25fps(1920×1080, 1280×960, 1280×720, 704×576, 640x480,352×288)
60Hz: 30fps(1920×1080, 1280×960, 1280×720, 704×576, 640x480,352×288)

Video Compression:

Main Stream: H.265+/H.265/H.264+/H.264

Sub-Stream:

H.265/H.264/MJPEG

Third Stream:

H.265/H.264/MJPEG

ROI encoding:

Support 4 areas with adjustable levels

Audio Compression:

G.711alaw/G.711ulaw/G.722.1/G.726/MP2L2/PCM

Audio Mode:

OFF/Audio input/Audio output

Protocols:

IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS,

Simultaneous Live View:	DDNS, NTP, RTSP,
Three-Stream:	RTCP, RTP, TCP, UDP,
Storage:	IGMP, ICMP, DHCP, PPPoE, Bonjour Up to 20 channels Support Built-in memory card slot, support Micro SD/SDHC/SDXC, up to 256 GB
User/Host:	Up to 32 users, 3 levels: Administrator, Operator and User
Security Measures:	User authentication (ID and PW), host authentication (MAC address)
Client GUI	
Client:	iVMS-4200, iVMS-4500, iVMS-5200, Hik-Connect
Web Browser:	IE 8 to 11, Chrome 31.0 to 44, Firefox 30.0 to 51
General	
Language:	English
Power Supply:	12VDC, PoE+
Power Consumption:	Max.: 18 W (Max. 7 W for IR)
Working	-30
Temperature/Humidity:	?-65?(-22?-149?)(outdoor)
Protection Level:	90% or less IP66 standard (outdoor dome) TVS 4,000V lightning protection, surge protection and voltage transient protection
Material:	ADC 12, PC, PC+10% GF

Dimensions:

? 164.5 mm × 290 mm (?
6.48" × 11.42")

Weight (approx.):

Approx. 2 kg (4.41 lb)