

# HIKVISION Camara mini PTZ 3MP IP 4X IP67 IK10 PoE RS485



**Marca:** Hikvision

**Código del producto:** 1942, DS-2DE3304W-DE

**Disponibilidad:** In Stock

**Peso:** 0.00kg

**Dimensiones:** 0.00cm x 0.00cm x 0.00cm

**HIKVISION**

## Short Description

- CMOS de barrido progresivo de 1 / 2,8 "
- 2048 x 1536P
- Zoom óptico 4X
- DWDR
- Soporte IP67 / IK10
- Soporte PoE (802.3af)
- Soporte RS485
- Soporte plug & play

## Descripción

- CMOS de barrido progresivo de 1 / 2,8 "
- 2048 x 1536P
- Zoom óptico 4X
- DWDR
- Soporte IP67 / IK10
- Soporte PoE (802.3af)
- Soporte RS485

- Soporte plug & play

#### Camera

Image Sensor:	1/2.8" Progressive Scan CMOS
Effective Pixels:	2048(H)x1536(V)
Minimum Illumination:	F1.6, AGC On : Color : 0.05 lux, B/W : 0.01 lux
White Balance:	Auto/Manual/ATW/Indoor /Outdoor/Daylight lamp/Sodium lamp
AGC:	Auto/Manual
BLC:	ON/OFF
HLC:	Support
WDR:	DWDR
Shutter Time:	1/1~1/10,000s
Day& Night:	ICR
Digital Zoom:	16X
Privacy Mask:	8 programmable privacy masks
Auto Focus:	Auto / Semi-automatic / Manual

#### Lens

Focal Length:	2.8~12mm, 4x
Zoom Speed:	Approx.1s(Wide~Tele)
Field of View:	105~33.5 degree (Wide~Tele)
Aperture Range:	F1.6 ~F2.7

#### Pan & Tilt

Pan Range:	Pan: 0~350°
Pan Speed:	Pan Manual Speed: 0.1°~60°/s
Tilt Range:	Tilt: 0°~90°
Tilt Speed:	Tilt Manual Speed: 0.1°~50°/s
Proportional Zoom:	Rotation speed can be adjusted automatically according to zoom

Number of Preset:	multiples 300
Power-off Memory:	Support
PTZ Position Display:	ON/OFF
Alarm	
Alarm Input:	1
Alarm Linkage:	Preset, Recording, Relay output, Upload center, Upload FTP, Email linkage
Input & Output	
Audio Input:	1 Mic in/Line in interface Line input: 2-2.4V[p-p]; output impedance: 1K?, ±10%
Audio Output:	1 Audio output interface Line level, impedance: 600?
Network	
Ethernet:	10Base -T, /100Base-TX, RJ45 Connector
Max.Image Resolution:	2048×1536
Main Stream:	50Hz:25fps (2048×1536,1 920×1080,1280×960,1280 ×720), 50fps (1280×960,1280×720) ; 60Hz:30fps(2048×1536,19 20×1080,1280×960,1280× 720), 60fps (1280×960,1280×720)
Sub Stream:	50Hz:25fps(704×576), 25fps(640×576), 25fps(320×288) 60Hz:30fps(704×480), 30fps(640×480), 30fps(320×240)
Third Stream:	50Hz: 25fps (1920 × 1080,

	1280 × 720, 704 × 576, 640 × 480, 320 × 288)
	60Hz: 30fps (1920 × 1080, 1280 × 720, 704 × 480, 640 × 480, 320 × 240)
Video Compression:	H.264 / MJPEG
ROI encoding:	Support 4 areas with adjustable levels
Audio Compression:	G.711ulaw/G.711alaw/G.7 26/MP2L2/G.722
Protocols:	IPv4/IPv6, HTTP, HTTPS, 802.1X, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP,IGMP, ICMP, DHCP, PPPoE
Simultaneous Live View:	Up to 20 channels
Storage:	Support up to 128GB Micro SD/SDHC/SDXC card. Support Edge recording
User/Host:	Up to 32 users,3 Levels: Administrator, Operator and User
Security Measures:	User authentication (ID and PW), Host authentication (MAC address) IP address filtering
Client GUI	
Date & Time Display:	Time: Week: Date, 6 formats on the Client
Client:	Support iVMS-4200
Web Browser:	IE 7+, Chrome 18 - 42, Firefox 5.0 +, Safari 5.02 +
General	
Language:	English
Power Supply:	12V DC & PoE((802.3af,

Power Consumption:

Working

Temperature/Humidity:

Protection Level:

Mounting:

Dimensions:

Weight (approx.):

Mount Option:

class3)

Max. 8W

-30°C ~ 65°C (-22°F ~  
149°F)

IP67, IK10, TVS 4,000V  
lightning protection, surge  
protection and voltage  
transient protection

Various mounting modes  
optional

140.7×107.2mm

950g

Wall mount: DS-1273ZJ

-PT6; In-ceiling Mount:

1227ZJ-PT6; Junction

Box: DS-1280ZJ -PT6