

# UNIVIEW Camara Domo IP 4MP lente fijo antivandalica



**Marca:**

**Código del producto:** 1931,  
IPC324LR3-VSPF28-D

**Disponibilidad:** In Stock

**Peso:** 0.00kg

**Dimensiones:** 0.00cm x 0.00cm x 0.00cm

## Short Description

- Day/night functionality
- Smart IR, up to 30 m (98 ft) IR distance
- 2D/3D DNR (Digital Noise Reduction)
- Ultra 265,H.265, H.264, MJPEG
- Triple streams
- ROI (Region of Interest)
- ONVIF Conformance
- Wide temperature range: -30°C to 60°C (-22°F to 140°F)

## Descripción

- Day/night functionality
- Smart IR, up to 30 m (98 ft) IR distance
- 2D/3D DNR (Digital Noise Reduction)
- Ultra 265,H.265, H.264, MJPEG
- Triple streams
- ROI (Region of Interest)
- ONVIF Conformance
- Wide temperature range: -30°C to 60°C (-22°F to 140°F)
- Wide voltage range of  $\pm 25\%$
- IK10 vandal resistant
- IP67
- 2-Axis

## Camera

Sensor 1/3", progressive scan, 4.0 megapixel, CMOS

Lens 2.8mm@F2.0

DORI	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
Distance	2.8	42	16.8	8.4	

Angle of View (H) 104.4°

Angle of View (V) 54.4°

Angle of View (O) 135.7°

AdjustmentPan 0° ~ 360°

angle

Shutter

Auto/Manual, 1 ~ 1/100000s

Minimum Illumination

0.03Lux (F2.0, AGC ON)

0Lux with IR

Day/Night IR-cut filter with auto switch (ICR)

Digital 2D/3D DNR

noise

reduction

S/N >52dB

IR Range Up to 30m (98ft) IR range

Defog Digital Defog

WDR DWDR

Video

Video Compression Ultra 265, H.265, H.264, MJPEG

H.264 code profile

Baseline profile, Main Profile

Frame Rate

Main Stream: 4MP (2592\*1520), Max 20fps;

Sub Stream: 720P (1280\*720), Max 20fps;

Third Stream: D1 (720\*576), Max 20fps

HLC Supported

BLC Supported

OSD Up to 4 OSDs

Privacy Mask Up to 8 areas

ROI Up to 2 areas

Motion Detection Up to 4 areas

Detection

## Network

Protocols IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS

Compatible ONVIF (Profile S, Profile T), API

## Integration

### Interface

Network 1 RJ45 100M Base-TX Ethernet

### General

Power DC 12V±25%, PoE (IEEE 802.3af)

Power consumption: Max 4W

Dimension 109 x 81mm (Ø4.3" x 3.2")

s (Ø x H)

Weight 0.35kg (0.77lb)

Working E -30°C ~ 60°C (-22°F ~ 140°F), Humidity: 95% RH (non-environment condensing)

Ingress IP67

### Protection

Vandal IK10

Resistant