

HIKVISION Camera Domo Network 3 MP IR Vari-focal 2.8mm to 12mm Easy IP



Marca: Hikvision

Código del producto: 1888, DS-2CD2735FWD-IZS(2.8-12mm

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

HIKVISION

Short Description

Cámara minidomo de tecnología IP y resolución 3 Megapíxeles (2048x1536 @25ips).

Óptica varifocal 2.8-12mm motorizada.

Compresión H.265+/H.265/H.264+/H.264.

Descripción

Cámara minidomo de tecnología IP y resolución 3 Megapíxeles (2048x1536 @25ips).

Óptica varifocal 2.8-12mm motorizada.

Compresión H.265+/H.265/H.264+/H.264.

- Sensor CMOS 1/2.8" ultra low light con conmutación día/noche mediante filtro mecánico.
- Sensibilidad en color 0,005 Lux Color (F1.2, AGC ON).
- LEDS IR alcance 30m.
- WDR real 120dB, BLC, Defog, EIS, 3D DNR, ROI.

Especificaciones de red:

- Salida Ethernet 10/100Mbps

- Triple streaming de video
- Servidor Web integrado Internet Explorer
- Compatible con ONVIF, ISAPI.
- Soporta tarjeta SD hasta 128GB (tarjeta no incluida).

Detección:

- Básica: movimiento, tamper de vídeo, excepciones.
- Avanzada: intrusión, cruce de línea, objeto abandonado, objeto sustraído, detección facial.

Especificaciones generales:

- Salida de video compuesto (75Ohm, BNC).
- Alarmas: 1 entrada y 1 salida, audio: 1 entrada y 1 salida.
- Nivel de protección: IP67, antivandálico IK10.
- Instalación en exterior.
- Alimentación 12 VDC max 750mA y PoE (802.3 af).
- Dimensiones: Ø 153.4 × L 133.1 mm.

Camera

Image Sensor:

1/2.8" Progressive Scan
CMOS

Signal System:

PAL/NTSC

Min. Illumination:

Color: 0.005 Lux @ (F1.2,
AGC ON), 0 Lux with IR
Color: 0.009 Lux @ (F1.6,
AGC ON), 0 Lux with IR

Shutter time:

1/3 s to 1/100,000 s

Slow shutter:

Support

Lens:

2.8 to 12 mm

Horizontal field of view:

97°to 33°

Vertical field of view: 69°to
25°

Diagonal field of view:

130°to 41°

Lens Mount:

?14

Adjustment Range:	Pan: 0° to 355°, tilt: 0° to 75°, rotate: 0° to 355°
Day& Night:	IR Cut Filter
Wide Dynamic Range:	120 dB
Digital noise reduction:	3D DNR
Focus:	Auto
Compression Standard	
Video Compression:	H.265+/H.265/H.264+/H.264/MJPEG
Video bit rate:	32Kbps~16Mbps
Audio Compression:	G.711/G.722.1/G.726/MP2L2/PCM
Audio bit rate:	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)
Triple Streams:	Yes
Image	
Max. Image Resolution:	2048×1536
Frame Rate:	50Hz: 25fps (2048 × 1536, 1920 × 1080, 1280 × 720) 60Hz: 30fps (2048 × 1536, 1920 × 1080, 1280 × 720)
Sub Stream:	50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)
Third Stream:	50Hz: 25fps (1280 × 720, 640 × 360, 352 × 288) 60Hz: 30fps (1280 × 720, 640 × 360, 352 × 240)
Image Enhancement:	BLC/3D DNR/BLC
Image Settings:	Rotate mode, saturation, brightness, contrast, sharpness and white balance adjustable by client software or web browser
ROI:	Support 1 fixed region for main stream and sub stream separately
Day/Night Switch:	Day/Night/Auto/Schedule/Tri

gged by Alarm In

Network

Network Storage:

microSD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR

Alarm Trigger:

Motion detection, tampering alarm, HDD full, HDD error, network disconnected, IP address conflicted, illegal login

Protocols:

TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

General Function:

One-key recovery, Anti-Flicker, three streams, heartbeat, mirror, password protection, video mask, Watermark, IP address filtering

System Compatibility:

ONVIF (Profile S, Profile G), ISAPI

Interface

Audio:

1 input (line in, 3.5 mm), 1 output (line out, 3.5 mm), mono sound

Communication Interface:

1 RJ45 10M / 100M Ethernet interface

Alarm:

1 alarm input, 1 alarm output (max. 12 VDC, 30 mA), terminal block

Video Output:

1Vp-p Composite Output(75%/CVBS) (For adjustment only)

On-board storage:

Built-in Micro SD/SDHC/SDXC slot, up to

Reset Button:	128 GB Yes
Audio Environment Noise Filtering: Audio Sampling Rate:	Support 8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz
Smart Feature-set Behavior Analysis:	Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection
Line Crossing Detection:	Cross a pre-defined virtual line
Intrusion Detection:	Enter and loiter in a pre-defined virtual region
Unattended Baggage:	Objects left over in the pre-defined region such as the baggage, purse, dangerous materials
Object Removal:	Objects removed from the pre-defined region, such as the exhibits on display.
Exception Detections: Recognition:	Scene change detection Face Detection
General Operating Conditions:	-30 °C ~ 60 °C (-22 °F ~ 140 °F) Humidity 95% or less (non-condensing)
Power Supply:	12 VDC ± 25%, PoE (802.3af Class3)
Power Consumption:	12 VDC, 0.75A, max. 9.5W PoE (802.3af, 36V to 57V), 0.1A to 0.3A, max. 11W
Impact Protection:	IK10
Weather Proof:	IP67
IR Range:	Up to 30m
Dimensions:	?153.4 × 133.1 mm (?6.04" ×

Weight:

5.24")

Camera: 1287 g (2.84 lb.)