

UNIVIEW 4MP Fisheye Fixed Dome Network Camera 431



Marca: Hikvision

Código del producto: 1691, IPC814SR-DVPF16

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Descripción

IPC814SR-DVPF16

Camera

Image sensor

1/3", progressive scan,4.0 megapixel, CMOS

Lens

1.6mm@ F1.6

Angle of View (H)

180°

Shutter

Auto/Manual?shutter time?1/6 s ~1/100000 s

Minimum Illumination

Colour: 0.01 Lux (F1.6, AGC ON)

0 Lux with IR

Day / Night

IR-cut filter for day & night function

Digital noise reduction

2D/3D DNR

S/N

>55dB

IR Range

UP to10m (33ft)

Defog

Digital Defog

WDR

120dB

Video

Compression

Ultra265, H.265, H.264,MJPEG

H.264 code profile

Baseline profile, Main Profile, High Profile

Frame Rate	Main Stream:(2560×1440): Max.25fps; Sub Stream:(1920×1080) : Max.25fps; Third Stream:D1(720 x 576): Max.25 fps
BLC	Supported
OSD	Up to 8 OSDs
ROI	Up to 8 areas
Privacy Mask	Up to 8 areas
Motion Detection	Up to 4 areas
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio	
Audio Compression	G.711
Two-way audio	Supported
Suppression	Supported
Sampling Rate	8 KHZ
Storage	
Edge Storage	Micro SD, up to 128GB
Network Storage	ANR
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible Integration	ONVIF(Profile S, Profile G), API
Live View Display	
Mount Type	Support table, wall, and ceiling
Interface	
Audio I/O	Audio interface

Input: impedance 35 k Ω ;
amplitude 2 V [p-p]
Output: impedance 600 Ω ;
amplitude 2 V [p-p]
3 built-in omnidirectional
microphone

1 / 1

Supported

Supported

1 BNC, impedance 75 Ω ;
amplitude 1 V [p-p]

1 RJ45 10M/100M Base-
TX Auto-adaptive

Ethernet

Alarm I/O

Built-in Mic

Built-in Speaker

Video Output

Network

General

Power

DC12V \pm 25%,PoE(IEEE
802.3af)

Power consumption: Max.
11 W

Dimensions (\varnothing x H)

125x 43.7 mm (4.9" x
1.7")

Weight

0.39kg(0.86lb)

Working Environment

-40 $^{\circ}$ C ~60 $^{\circ}$ C (-40 $^{\circ}$ F ~
140 $^{\circ}$ F), Humidity
:10%~95% RH

Ingress Protection

IP66

Vandal Resistant

IK10

Reset Button

Supported