

HIKVISION NVR 32ch PoE 4 SATA

Marca: Hikvision

Código del producto: 1949, DS-7732NI-E4/16P

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm



HIKVISION®

Short Description

- Cámaras de red de terceros compatibles
- Resolución de hasta 6 megapíxeles de grabación.
- Salida HDMI y VGA a hasta 1920 × 1080P resolución
- Hasta 4 interfaces SATA Plug & Play con hasta 16 redes PoE independientes interfaces
- Soporte de detección de red, incluido el retardo de red, pérdida de paquetes, etc.

Descripción

- Cámaras de red de terceros compatibles
- Resolución de hasta 6 megapíxeles de grabación.
- Salida HDMI y VGA a hasta 1920 × 1080P resolución
- Hasta 4 interfaces SATA Plug & Play con hasta 16 redes PoE independientes interfaces
- Soporte de detección de red, incluido el retardo de red, pérdida de paquetes, etc.

Video/Audio Input

Two-way audio input:

1-ch, RCA (2.0 Vp-p, 1k?)

IP video input:

32-ch

Network

Remote connection:

128

Incoming bandwidth:	160Mbps
Outgoing bandwidth:	80Mbps
Video/Audio Output HDMI/VGA output:	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
Recording Resolution:	6MP/5MP/4MP/3MP/1080 P/UXGA/720P/VGA/4CIF /DCIF/2CIF/CIF/QCIF
Frame Rate:	Main stream: 50 fps (P) / 60 fps (N) Sub-stream: 50 fps (P) / 60 fps (N)
Audio Output: Synchronous Playback:	1-ch, RCA (Linear, 1k?) 16-ch
Decoding Capability:	16-ch@4CIF, 12-ch@720P, 6-ch@1080P
Live view / Playback:	6MP/5MP/3MP/1080P/UX GA/720P/VGA/4CIF/DCI F/2CIF/CIF/QCIF
Hard Disk SATA:	4 SATA interfaces for 2 HDDs + 1 DVD-R/W (default), or 4HDDs
Capacity:	Up to 6TB capacity for each HDD
External Interface Network Interface:	1RJ-45 10/100/1000Mbps self-adaptive Ethernet

USB Interface:	interface Front panel: 2 × USB 2.0 Rear panel: 1 × USB 3.0
Alarm In:	16-ch
Alarm Out:	4-ch
POE	
Supported Standard:	AF and AT
Interface:	16 independent 100 Mbps PoE network interfaces
Max. Power:	200W
General	
Power Supply:	100~240VAC
Consumption(without hard disk and POE):	? 20W
Working Temperature:	-10 oC ~ +55 oC (+14 oF~ + 131 oF)
Working Humidity:	10 % ~ 90 %
Chassis:	19-inch rack-mounted 1.5U chassis
Dimensions:	445 × 390 × 70mm (17.5 ×15.3 × 2.8 inch)
Weight(without HDD):	? 4 Kg (8.82 lb)