

NVR 8CH H.265 1 x 4K@3060



Marca:

Código del producto: 1677, NVR301-08L-P8

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Short Description

- 4/8/16-channel input
- Plug & Play with 4/8 independent PoE network interfaces
- Third-party IP cameras supported with ONVIF conformance
- Support 1-ch HDMI, 1-ch VGA, HDMI at up to 4K(3840×2160) resolution
- Up to 8 Megapixels resolution recording
- Support H.265/H.264 video formats
- Accurate retrieval, instant playback
- 1 SATA HDD up to 6 TB
- Support for P2P, UPnP, NTP, DHCP, PPPoE

Descripción

- 4/8/16-channel input
- Plug & Play with 4/8 independent PoE network interfaces
- Third-party IP cameras supported with ONVIF conformance
- Support 1-ch HDMI, 1-ch VGA, HDMI at up to 4K(3840×2160) resolution
- Up to 8 Megapixels resolution recording
- Support H.265/H.264 video formats
- Accurate retrieval, instant playback
- 1 SATA HDD up to 6 TB
- Support for P2P, UPnP, NTP, DHCP, PPPoE

Model	NVR301-04L-P4	NVR301-08L-P8	NVR301-16L-P8
Video/Audio Input			
IP Video Input	4-ch	8-ch	16-ch

Two-way 1-ch, RCA

Audio Input

Network

Incoming 40Mbps 60Mbps 60Mbps

Bandwidth

Outgoing 64Mbps 64Mbps 80Mbps

Bandwidth

Remote 128

Users

Video/Audio Output

HDMI/VGA HDMI:

Output

4K (3840x2160) /30Hz, 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz

VGA:

1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz

Recording 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Resolution

Audio Output 1-ch, RCA

Synchronous 4-ch 8-ch 16-ch

Playback

Decoding

Compression H.265/H.264

Live view/ 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Playback

Capability 1 x 4K@30, 3 x 4MP@20, 4 x 1080p@25, 8 x 720p@25, 16 x D1

Hard Disk

SATA 1 SATA interface

Capacity up to 6TB for each disk

External Interface

Network 1 RJ-45 10M/100M self-adaptive Ethernet Interface

Interface

USB Rear panel? 2 x USB2.0

Interface

PoE

Interface 4 independent 100 Mbps PoE network interfaces 8 independent 100 Mbps PoE network interfaces

Max Power Max 30W for single port Max 30W for single port

Max 54W in total (13.5W for each)
Max 108W in total (13.5W for each)

Supported Standard IEEE 802.3at, IEEE 802.3af

General

Power Supply 48V DC 52V DC

Consumption ? 8 W

(without HDD)

Working Temperature -10°C ~ + 55°C (+14°F ~ +131°F)

Working Humidity 10% ~ 90%

Dimensions 42 × 205 × 205mm (1.7" × 8.1" × 8.1")

Weight (without HDD)

0.59kg (1.3 lb) ? 0.68 Kg (1.50 lb)

)