

HIKVISION Camara Bullet 2 MP Ultra-Low Light Smart IR IP67



Marca: Hikvision

Código del producto: 1956, DS-2CE16D8T-IT3ZF (2.7-13.

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

HIKVISION®

Short Description

- CMOS de alto rendimiento de 2 megapíxeles
- Luz ultrabaja
- Resolución 1920 × 1080
- Enfoque automático, lente varifocal motorizada de 2,7-13,5 mm
- WDR verdadero de 130 dB, 3D DNR
- Smart IR, hasta 60 m de distancia IR
- IP67
- Up the Coax (HIKVISION-C)
- Salida de video 4 en 1 (TVI / AHD / CVI / CVBS conmutable)
-

Descripción

- CMOS de alto rendimiento de 2 megapíxeles
- Luz ultrabaja
- Resolución 1920 × 1080
- Enfoque automático, lente varifocal motorizada de 2,7-13,5 mm

- WDR verdadero de 130 dB, 3D DNR
- Smart IR, hasta 60 m de distancia IR
- IP67
- Up the Coax (HIKVISION-C)
- Salida de video 4 en 1 (TVI / AHD / CVI / CVBS conmutable)

Camera

Image Sensor:	2MP CMOS Image Sensor
Signal System:	PAL/NTSC
Effective Pixels:	1920(H)*1080(V)
Shutter Time:	1/25(1/30) s to 1/50,000 s
Lens Mount:	?14
Adjustment Range:	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°
Day& Night:	IR cut filter
Video Frame Rate:	1080p@25fps/1080p@30f ps
Synchronization:	Internal Synchronization
Up the Coax:	Support

Menu

Auto White Balance:	Auto / Manual
BLC:	Support
AGC:	Support
Language:	English/Chinese

General

Operating Conditions:	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non- condensing)
Power Supply:	12 VDC ±25%;-A: 12 VDC ±25%, 24 VDC ±25% *You are recommended to use one power adapter to supply the power for one camera.
Weather Proof:	IP67
IR Range:	Up to 60m
Communication :	Up the coax

Dimension:

Weight:

Protocol: HIKVISION-
C(Coaxitron)

85 mm × 92 mm × 269.6
mm (3.3" × 3.6" × 10.6")

Approx. 910 g (2.01 lb.),
-A: Approx. 940 g (2.07
lb.)