

HIKVISION Camara Domo 5MP VF EXIR IP67 IK10



HIKVISION

Marca: Hikvision

Código del producto: 1953, DS-2CE56H0T-VPIT3ZF (2.7-1

Disponibilidad: In Stock

Peso: 0.00kg

Dimensiones: 0.00cm x 0.00cm x 0.00cm

Short Description

- CMOS de alto rendimiento de 5 megapíxeles
- Salida analógica HD, hasta 5MP de resolución.
- Lente varifocal motorizada de 2.7-13.5mm
- Verdadero día / noche
- Menú OSD, 2D DNR, DWDR
- Tecnología EXIR, hasta 40m de distancia IR.
- IP67, IK10
- Salida de video 4 en 1 (TVI / AHD / CVI / CVBS conmutable)
- Up the Coax (HIKVISION-C)

-

Descripción

- CMOS de alto rendimiento de 5 megapíxeles
- Salida analógica HD, hasta 5MP de resolución.
- Lente varifocal motorizada de 2.7-13.5mm
- Verdadero día / noche

- Menú OSD, 2D DNR, DWDR
- Tecnología EXIR, hasta 40m de distancia IR.
- IP67, IK10
- Salida de video 4 en 1 (TVI / AHD / CVI / CVBS conmutable)
- Up the Coax (HIKVISION-C)

Camera

Image Sensor:	5MP CMOS Image Sensor
Effective Pixels:	2560 (H) × 1944 (V)
Shutter Time:	1/25(1/30) s to 1/50,000 s
Lens Mount:	φ14
Adjustment Range:	Pan: 0° to 355°; Tilt:0° to 75°; Rotate: 0° to 355°
Day& Night:	IR cut filter with auto switch
Video Frame Rate:	PAL: 5 MP@20fps, 4 MP@25fps, 1080p@25fps; NTSC: 5 MP@20fps, 4 MP@30fps, 1080p@30fps
HD Video Output:	1 Analog HD output
Synchronization:	Internal Synchronization

Menu

D/N Mode:	Auto / Color / B/W
Auto White Balance:	Auto/MWB
BLC:	Support
AGC:	Support

General

Operating Conditions:	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply:	12 VDC±15%, 24 VAC±15%
Impact Protection:	IK10.
Weather Proof:	IP67
IR Range:	Up to 40m
Communication :	Up the coax Protocol: HIKVISION-

Dimension:

C(Coaxitron)
Ø 145.2 mm × 124.1 mm (
Ø 7.1" × 4.9")

Weight:

DS-2CE56H0T-VPIT3ZF:
Approx. 610 g (1.34 lb.)
DS-2CE56H0T-
AVPIT3ZF: Approx. 655 g
(1.44 lb.)