

# HIKVISION Control de asistencia 1000 usuarios huellas / EMcard



**HIKVISION**

**Marca:** Hikvision

**Código del producto:** 1970, DS-K1T606MF

**Disponibilidad:** In Stock

**Peso:** 0.00kg

**Dimensiones:** 0.00cm x 0.00cm x 0.00cm

## Short Description

System Parameters

1:N Face Recognition Duration: ? 1 s/Person

Operation System: Linux

Fingerprint Module: Optical, Red Backlight

## Descripción

System Parameters

1:N Face Recognition Duration: ? 1 s/Person

Duration:

Operation System: Linux

Fingerprint Module: Optical, Red Backlight

Card Capacity:	5,000
Face Recognition Accuracy Rate:	? 99%
Card Type:	M1 Card
Camera:	2 MP; WDR; Wide-Angle Lens
Fingerprint Capacity:	5,000
Event Capacity:	100,000
Face Recognition Distance:	0.3 m to 1 m
Face Capacity:	3,200
Device Interfaces	
Communication Mode:	Ethernet 10/100Mbps Self-adaptive; Wi-Fi
Output Interface:	Lock Relay × 1, Alarm Relay × 1
Input Interface:	RS-485 × 1, Wiegand × 1, USB × 1, Exit Button × 1, Tamper × 1 , Alarm Input × 2
General	
LCD Screen:	5-inch LCD Touch Screen; Resolution: 480 × 800
Power Supply:	12 VDC/2 A (Centralized Power Supply)
Protection Level:	IP 65 Water-Proof
Installation:	Wall Mounting with/without Gang Box
Application Situation:	Indoor; Outdoor
Working Humidity:	10% to 90% (Non-Condensing)
Working Temperature :	-20°C to +50°C (-4°F to 122°F)
Dimensions (L×W×H):	281.5mm × 113mm × 45mm (11.08" × 4.45" × 1.77")